

B1232 v. 1.0
SoftBaugh, Inc.
4080 McGinnis Ferry Road
Suite 604
Alpharetta, GA 30005 USA

2 Layers
PCB 0.062 +/- 0.005 FR4
0.008 traces, 0.008 spaces
Finish: HASL
All holes plated through
1 oz copper
Soldermask LPI
Silkscreen White
See ReadMe.txt for layer info
Aperture Files as .Axx
Gerber Files as .Gxx

B1232.abl Aperture bottom layer
B1232.atl Aperture top layer
B1232.atp Aperture top paste
B1232.abs Aperture bottom solder mask
B1232.ats Aperture top solder mask
B1232.ato Aperture top silkscreen
B1232.am1 Aperture mechanical 1 (board outline)
B1232.am4 Aperture mechanical 4 (documentation)
B1232.ad1 Aperture drill guide
B1232.gto Top Silkscreen
B1232.gbl Bottom layer
B1232.gtl Top layer
B1232.gtp Top paste
B1232.gts Top solder mask
B1232.gbs Bottom solder mask
B1232.gm1 Mechanical 1 (Board outline)
B1232.gm4 Mechanical 4 (documentation)
B1232.gd1 Drill guide
B1232.drr Text drill report
B1232.dr1 Drill file
B1232.txt Text drill file

Drill Drawing See Additional Notes as .gm4

