

BLCDA4 v. 1.0
 SoftBaugh, Inc.
 4080 McGinnis Ferry Road
 Suite 604
 Alpharetta, GA 30004 USA
 2 Layers
 PCB 0.062 +/- 0.005 FR4
 0.008 traces, 0.008 spaces
 Finish: HASL
 All holes plated through
 1 oz copper
 Soldermask LPI
 Silkscreen White
 See ReadMe.txt for layer info
 Aperture Files as .axx
 Gerber Files as .gxx

BLCDA4.abl Aperture bottom layer
 BLCDA4.atl Aperture top layer
 BLCDA4.abs Aperture bottom solder mask
 BLCDA4.ats Aperture top solder mask
 BLCDA4.ato Aperture top silkscreen
 BLCDA4.am1 Aperture mechanical 1 (board outline)
 BLCDA4.am4 Aperture mechanical 4 (documentation)
 BLCDA4.ad1 Aperture drill guide
 BLCDA4.gto Top Silkscreen
 BLCDA4.gbl Bottom layer
 BLCDA4.gtl Top layer
 BLCDA4.gts Top solder mask
 BLCDA4.gbs Bottom solder mask
 BLCDA4.gm1 Mechanical 1 (Board outline)
 BLCDA4.gm4 Mechanical 4 (documentation)
 BLCDA4.gd1 Drill guide
 BLCDA4.drr Text drill report
 BLCDA4.dr1 Drill file
 BLCDA4.txt Text drill file

Drill Drawing See Additional Notes as .gm4

