

DZ1611 v1.1
 SoftBaugh, Inc.
 4080 McGinnis Ferry Road
 Suite 604
 Alpharetta, GA 30005 USA

2 Layers
 PCB 0.062 +/- 0.005 FR4
 0.008 traces, 0.008 spaces
 Finish: HASL
 All holes plated through
 1 oz copper
 Soldermask LPI
 Silkscreen White
 See ReadMe.txt for layer info
 Aperture Files as .Axx
 Gerber Files as .Gxx

DZ1611.abl Aperture bottom layer
 DZ1611.atl Aperture top layer
 DZ1611.abs Aperture bottom solder mask
 DZ1611.ats Aperture top solder mask
 DZ1611.ato Aperture top silkscreen
 DZ1611.am1 Aperture mechanical 1 (board outline)
 DZ1611.am4 Aperture mechanical 4 (documentation)
 DZ1611.ad1 Aperture drill guide
 DZ1611.gto Top Silkscreen
 DZ1611.gbl Bottom layer
 DZ1611.gtl Top layer
 DZ1611.gts Top solder mask
 DZ1611.gbs Bottom solder mask
 DZ1611.gm1 Mechanical 1 (Board outline)
 DZ1611.gm4 Mechanical 4 (documentation)
 DZ1611.gd1 Drill guide
 DZ1611.drr Text drill report
 DZ1611.dr1 Drill file
 DZ1611.txt Text drill file

Drill Drawing See Additional Notes as .gm4

